

DATA SHEET

COD. 6721W

MINI COLOUR HANDS-FREE MONITOR. WHITE. SBTOP SYSTEM

Wall-mounted monitor with 4.3" 16/9 colour screen and handset. Allows brightness control, plus adjustment of the ringtone volume, which can be customised by choosing one of several different melodies. Equipped with 4 soft-touch buttons for lock-release, self-ignition, switchboard call and privacy function management as standard, and with door status indicator LED. Manages floor door calls as standard. Option of adding 4 additional buttons with accessory Art. 6733W. Complete with 2 x 8-position DIP-SWITCHES for user code programming and button programming. The wall-mounting or residential series box backplate and riser distribution terminal Art. 1214/2C are included. The monitor can only be used in 2-wire SimplebusTop Colour systems. Dimensions 115x160x22 mm.



General specifications

System:	SBT(2-wires)
Audio/video system:	Yes
Wall-mounted:	Yes
Desk base-mounted:	Yes
Hands-free function:	Yes
Type of display:	LCD
Display size (inches):	4,3" 16/9
Display resolution (H x V):	480x272pixel
B/W or colour display:	Color
Product color:	White
Buttons with technology cap sense:	Yes
Sensitive Touch technology:	Yes
Total buttons:	5
Additional buttons:	3
LED signaling:	3
Backlighting color:	White

Functions

Actuator control function:	Yes
Self-ignition:	Yes
Switchboard call function:	Yes
Panic call:	Yes
Intercom function:	Yes
Selective intercom call:	Yes
Call to multiple addresses:	Yes
Privacy function:	Yes

DATA SHEET

Doctor:	Yes
Floor door call function:	Yes
Electronic bell:	Yes
Customisable ringtone:	Yes
Privacy conversation function:	Yes
Key button function:	Yes
Full Duplex hands-free function:	Yes

Hardware specifications

Removable terminals:	Yes
----------------------	-----

Settings

Loudspeaker volume control:	Yes
Microphone volume control:	Yes
Ringtone volume control:	Yes
Display brightness control:	Yes
Display contrast control:	Yes
Display colour control:	Yes

General info

Product height (mm):	160
Product width (mm):	115
Product depth (mm):	22

Compatibility

Video door entry family:	Yes
Simplebus Top system:	Yes
Simplebus Color system:	Yes

Technical specifications

Supply voltage:	22÷28Vdc
Absorption:	2
Maximum current absorption (mA):	325
Microphone:	6mm omni-direction
Speaker:	36mm 40Ohm 1W
IP Rating:	30
Operating temperature (°C):	-5÷40
Video encoding:	PAL / NTSC
Product weight (g):	0,533
Clamps:	L L CFP1 CFP2

Packaging

Single pack height (mm):	63
--------------------------	----

DATA SHEET

Single pack width (mm):	212
Single pack depth (mm):	188
Single pack volume (dm3):	2,51