



UT8090

ULTRA VIP VIDEO+TOUCH COMPLETE ENTRANCE PANEL



Ultra series flush-mounted audio/video entrance panel with 5" touch-screen module, for IP (ViP) system. Twilight sensor for touch-screen backlighting management. Omnidirectional digital microphone and dual loudspeaker for high-fidelity audio. Wide-angle colour video camera with 160° horizontal and 100° vertical field of vision. Audio-visual indications for disabled individuals assistance request. 5" capacitive display with high visibility and impact-proof glass, plus white or black theme selection. Easy-to-use graphic interface, can be customised with virtual call buttons or with a number keypad to call users when the relevant code is known. Access control function with activation of the audio or audio/video module outputs and the system actuators. Buttons can be customised for direct calls to the switchboard, commercial activities with corresponding logos and to display welcome messages. Has a Wiegand output for interfacing with access control systems, an RFID reader for activation of an opening using keys or Comelit cards and a Bluetooth connection. Consists of audio/video module art. UT8020, Touch module art. UT9270, frame art. UT9163 and flush-mounted box art. 3110/3. 10 mm protrusion from the wall. Dimensions (L x H x D): 125.5x317.5x55 mm.

AWARDS



UT8090

ULTRA VIP VIDEO+TOUCH COMPLETE ENTRANCE PANEL



DESIGN
MILANO



UT8090

ULTRA VIP VIDEO+TOUCH COMPLETE ENTRANCE PANEL

GENERAL DATA

Type	Modular
Height (inch) (pc)	75
Width (inch) (pc)	29.65
Depth (inch) (pc)	8.27
Product weight (oz) (oz)	70.55
Product color	Black RAL9005, Aluminum
Flush-mounted	Yes

COMPATIBLE SYSTEMS

ViP	Yes
-----	-----

DISPLAY

Display type	TFT
Display size (")	5
Touch screen	Yes, capacitive
Resolution (pixel)	800x480

AUDIO FEATURES

Microphone	MEMS audio digital sensor, omnidirectional
Loudspeaker	28mm (Ø), 8 Ohm, 1W (2)
Technologies implemented	Echo canceling

CAMERA FEATURES

Camera	Colors
Sensor type	1/3" CMOS
Lens optical dimensions (pc)	0.59
Angle of view (H x V - °)	160 x 100
Resolution (H x V - pixel)	1024x608 (max video stream resolution)
Video compression	H.264



UT8090

ULTRA VIP VIDEO+TOUCH COMPLETE ENTRANCE PANEL

ELECTRICAL CHARACTERISTICS

Type of power supply	PoE, External power supply
Supply voltage	33VDC
PoE power supply	Standard IEEE 802.3af, Comelit PoE (56VDC)
PoE class	Class 0
Absorption in stand-by (W)	7
Maximum absorption (W)	14

HARDWARE FEATURES

Call type	Push-buttons, Digital
Type of buttons	Capacitive
Backlight color	White, Black
Clamps	RTE GND/SE- SE+ NO NC COM V- V+ - + TX- TX+ RX- RX+ D1+ D1- D2+ D2- GND D0 D1 GND IN
Number of inputs (n°)	1
Number of outputs (n°)	2
Integrated proximity reader	RFID Mifare Classic
Communication ports	Micro-USB, 1 x Wiegand, 2 x RS485, Ethernet
Twilight sensor	Yes

SETTINGS

Loudspeaker volume	Yes
Microphone volume	Yes
Backlight brightness	Yes



UT8090

ULTRA VIP VIDEO+TOUCH COMPLETE ENTRANCE PANEL

NETWORK AND COMMUNICATION PROTOCOLS

Type of LAN network	Ethernet 10 Mbit/s
IP address assignment	Auto IP, DHCP, Static
Bluetooth	Yes
Wiegand	Keypad: 4 bits for each digit, without parity, adding the "B" digit at the end. Comelit Cards/Keys: 26 bit

PROGRAMMING MODE

ViP Manager software	Yes
----------------------	-----

ENVIRONMENTAL AND COMPLIANCE FEATURES

IP protection rating	IP65
Vandal Resistant rating (IK code)	IK08
Operating temperature (°F) (°F)	-13 ÷ 131
Operating humidity (RH max) (%)	25 ÷ 95
Environmental class	IV
CE certifications	RoHS II - 2011/65/UE (EN 50581:2012), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)

MAIN FUNCTIONS

Door opener	Yes
Input for local door release button	Yes
Door open signaling input	Yes
Access control via proximity reader	Yes
Access control via door opener code	Yes
No. of storable users (n°)	4000
Number of door opener codes (n°)	4000
Number of storable proximity keys	4000
Visual indications of system status	Yes
Acoustic signals of system status	Yes
Speech synthesis of system status	Yes



UT8090

ULTRA VIP VIDEO+TOUCH COMPLETE ENTRANCE PANEL

MAIN FUNCTIONS

Customizable welcome message	Yes
Customisable image of the button	Yes

GENERAL FEATURES

Switchboard call function	Yes
Actuator control function	Yes
Type of finishing materials	Polycarbonate, Glass, Aluminium alloy